



# 1500VDC 1 INPUT FUSED TRUNK BUSS

## ABOUT

Olson Motor & Control 1500VDC 1 Input Fused, Trunk Buss Combiner Box .  
Designed for 1 positive input trunk cable, 2XL/3L blade sizing, 125-400A.

## SPECIFICATIONS

VOLTAGE	1500VDC
AMPERAGE	400 AMP
POSITIVE FUSE AMPERAGE RATING RANGE	125, 160, 200, 250, 315, 355, 400A
DISCONNECT KA RATING	10 KAIC
INPUTS	1
POSITIVE TRUNK INPUT CONNECTION	M10 SINGLE HOLE LUGS, CU ONLY
NEGATIVE TRUNK OUTPUT CONNECTION	M10 SINGLE HOLE LUGS, CU ONLY
POSITIVE & NEGATIVE TO INVERTER CABLE RANGES	M10 - M12, SINGLE HOLE LUG, 4/0 - 750KCMIL
STANDARD/COMPLIANCE	UL1741
STANDARD ENCLOSURE	NEMA4 PAINTED STEEL
STANDARD FEATURES	LEXAN SAFETY SHIELD, SURGE PROTECTION, OMC MOUNTING BRACKETS, NEMA4X BREATHER DRAIN




## OPTIONS

NEMA4 X FIBERGLASS ENCLOSURES	2-HOLE OUTPUT LUG PROVISIONS
PRE-PUNCHED CONDUIT ENTRY	FACTORY INSTALLED CABLE GLANDS

## CONTACT INFO

1908 AEROTECH DR. SUITE 150  
COLORADO SPRINGS, CO

 908-231-1500

 SALES@OLSONMC.COM